

There is described a low-foaming, nonsilicone, aqueous textile auxiliary composition comprising: (a) a homopolymer of an ethylenically unsaturated sulfonic or carboxylic acid or an anhydride thereof, (b) a nonionic surfactant of formula (1), wherein K is an aliphatic radical of at least 8 carbon atoms, R₁ is hydrogen, C₁-C₈alkyl, a cycloaliphatic radical of at least 5 carbon atoms, styryl, an unsubstituted or halogen substituted C₁-C₁₀alkylisocyanato or an unsubstituted or by a heteroatom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical, "alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and p is an integer from 2 to 60, and optionally (c) a hydrotropic agent. The textile auxiliary composition is suitable for use as dispersants and for wetting, washing and/or bleaching fibre materials.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT Austria
 AU Australia
 BB Barbados
 BE Belgium
 BF Burkina Faso
 BG Bulgaria
 BJ Benin
 BR Brazil
 CA Canada
 CF Central African Republic
 CG Congo
 CH Switzerland
 CI Côte d'Ivoire
 CM Cameroon
 CS Czechoslovakia
 DE Germany
 DK Denmark
 ES Spain

FI Finland
 FR France
 GA Gabon
 GB United Kingdom
 GN Guinea
 GR Greece
 HU Hungary
 IE Ireland
 IT Italy
 JP Japan
 KP Democratic People's Republic
 of Korea
 KR Republic of Korea
 LI Liechtenstein
 LK Sri Lanka
 LU Luxembourg
 MC Monaco
 MG Madagascar

ML Mali
 MN Mongolia
 MR Mauritania
 MW Malawi
 NL Netherlands
 NO Norway
 PL Poland
 RO Romania
 RU Russian Federation
 SD Sudan
 SE Sweden
 SN Senegal
 SU Soviet Union
 TD Chad
 TG Togo
 US United States of America


Aqueous textile auxiliary composition

The present invention relates to a low-foaming, nonsilicone, aqueous textile auxiliary composition, to its preparation and to the versatile use as wetting agent, detergent, dispersant or as stabiliser in peroxide bleaching liquors.

The novel low-foaming, aqueous textile auxiliary composition comprises

(a) a homopolymer of an ethylenically unsaturated sulfonic or carboxylic acid or an anhydride thereof,

(b) a nonionic surfactant of formula



wherein

R is an aliphatic radical of at least 8 carbon atoms,

R₁ is hydrogen, C₁-C₈alkyl, a cycloaliphatic radical of at least 5 carbon atoms, styryl, an unsubstituted or halogen substituted C₁-C₁₀alkylisocyanato or an unsubstituted or by a hetero atom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical,

"alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and

p is an integer from 2 to 60, and optionally

(c) a hydrotropic agent.

Because of its low-foaming properties the inventive textile auxiliary composition is free of silicon.

Ethylenically unsaturated monomeric sulfonic or carboxylic acids are suitable for preparing the homopolymers eligible for use as component (a). Monocarboxylic acids and dicarboxylic acids and anhydrides thereof as well as sulfonic acids may suitably be used, each of which acids contains an ethylenically unsaturated aliphatic radical and preferably

- 2 -

not more than 7 carbon atoms. Monocarboxylic acids of 3 to 5 carbon atoms are preferred, typically acrylic acid, methacrylic acid, α -haloacrylic acid, 2-hydroxyethylacrylic acid, α -cyanoacrylic acid, crotonic acid and vinylacetic acid. Ethylenically unsaturated dicarboxylic acids are preferably fumaric acid, maleic acid or itaconic acid, and also mesaconic acid, citraconic acid, glutaconic acid and methylmalonic acid. The preferred anhydride of these acids is maleic anhydride.

Suitable monomeric sulfonic acids which can be used for the homopolymerisation of component (a) include vinylsulfonic acid or 2-acrylamido-2-methylpropanesulfonic acid. Preferred polymerised carboxylic acids are polymethacrylic acid and, more particularly, polyacrylic acid. The polyacrylic acids to be used in the practice of this invention have a molecular weight in the range from 4000 to 2 000 000, preferably from 4 500 to 800 000.

The homopolymers eligible for use as component (a) of the novel composition are prepared by methods which are known per se, conveniently by polymerising the appropriate monomer in the presence of a catalyst, suitably in the temperature range from 60 to 100°C.

The catalyst is preferably an initiator which forms free radicals. Illustrative examples of suitable initiators for carrying out the reaction are symmetrical aliphatic azo compounds such as azobisisobutyronitrile, azobis(2-methylvaleronitrile), 1,1'-azobis(1-cyclohexanitrile) and alkyl 2,2'-azobisisobutyrate, symmetrical diacyl peroxides, such as acetyl, propionyl or butyryl peroxide, benzoyl peroxide, bromine-, nitro-, methyl- or methoxy-substituted benzoyl peroxides as well as lauroyl peroxide; symmetrical peroxydicarbonates such as diethyl, diisopropyl, dicyclohexyl and dibenzyl peroxydicarbonate; tert-butyl peroctoate, tert-butyl perbenzoate or tert-butylphenyl peracetate as well as peroxycarbamates such as tert-butyl-N-(phenylperoxy)carbamate or tert-butyl-N-(2,3-dichloro- or -4-chlorophenylperoxy)carbamate. Further suitable peroxides are: tert-butylhydroperoxide, di-tert-butylperoxide, cumene hydroperoxide, dicumene peroxide and tert-butyl perpivalate. A further suitable compound is potassium persulfate, which is preferably used in the practice of this invention.

The catalysts are normally used in amounts of 0.1 to 10 % by weight, preferably 0.5 to 2 % by weight, based on the starting materials.

It is advantageous to carry out the polymerisation reaction in an inert atmosphere,

- 3 -

conveniently in a nitrogen atmosphere.

The substituent R in formula (1) is conveniently the hydrocarbon radical of an unsaturated or saturated aliphatic monoalcohol of 8 to 22 carbon atoms. The hydrocarbon radical may be straight chain or branched. Preferably R is an alkyl or alkenyl radical of 9 to 14 carbon atoms.

The aliphatic saturated monoalcohols which may be suitably used are typically lauryl alcohol, myristyl alcohol, cetyl alcohol or stearyl alcohol, as well as synthetic alcohols such as 2-ethylhexanol, 1,1,3,3-tetramethylbutanol, octan-2-ol, isononyl alcohol, trimethylhexanol, trimethylnonyl alcohol, decanol, C₉-C₁₁oxoalcohol, tridecyl alcohol, isoridecanol or linear primary alcohols (Alfols) of 8 to 18 carbon atoms. Some representatives of these Alfols are Alfol (8-10), Alfol (9-11), Alfol (10-14), Alfol (12-13) or Alfol (16-18). ("Alfol" is a registered trademark).

Illustrative examples of unsaturated monoalcohols are dodecenyl alcohol, hexadecenyl alcohol or oleyl alcohol.

C₁-C₁₀Alkyl denotes straight-chain or branched hydrocarbon radicals, typically methyl, ethyl, n-propyl, isopropyl, n-butyl, sec-butyl, tert-butyl, amyl, isoamyl or tert-amyl, heptyl, octyl, isooctyl, nonyl or decyl. Preferred radicals are those which contain 1 to 5, preferably 1 to 4, carbon atoms.

Cycloalkyl denotes cyclobutyl, cyclopentyl, cyclohexyl, cycloheptyl or cyclooctyl.

Examples of C₁-C₁₀Alkylisocyanato radicals are methylisocyanato, ethylisocyanato, 2-chlorethylisocyanato, n-propylisocyanato, isopropylisocyanato, n-butylisocyanato, sec-butylisocyanato, tert-butylisocyanato, amylisocyanato, isoamylisocyanato, tert-amylisocyanato, heptylisocyanato, octylisocyanato, isooctylisocyanato, nonylisocyanato or decylisocyanato.

Examples for hetero atoms are oxygen, nitrogen or sulfur. Oxygen is preferred.

Cycloalkylisocyanato radicals denote 4 to 8, preferably 5 to 7 carbon atoms. Examples for these radicals are cyclobutylisocyanato, cyclopentylisocyanato, cyclohexylisocyanato,

- 4 -

methylcyclohexylisocyanato, ethylcyclohexylisocyanato, hexylcycloisocyanato, cycloheptylisocyanato or cyclooctylisocyanato. Preferred cycloalkylisocyanato radical is cyclohexylisocyanato.

The alcohol radicals may be single or in the form of mixtures of two or more components, such as mixtures of alkyl and/or alkenyl groups which are derived from soybean fatty acids, palm nut fatty acids or tallow oils.

(Alkylene-O)_p chains are preferably of the ethylene glycol, ethylene propylene glycol or ethylene isopropylene glycol type; p is preferably 4 to 20.


The polyadducts of unsaturated or saturated aliphatic monoalcohols and ethylene oxide may be further reacted with C₁-C₁₀alkylisocyanates to give end-capped nonionic surfactants.

Illustrative examples of nonionic surfactants are:

- polyadducts of preferably 2 to 60 mol of alkylene oxides, preferably ethylene oxide, individual ethylene oxide units of which polyadducts can be replaced by substituted epoxides, such as buten-1-oxide or butene-2-oxide and/or propylene oxide, with higher unsaturated or saturated fatty alcohols of 8 to 22 carbon atoms.

- The reaction products of the polyadducts of preferably 2 to 60 mol of alkylene oxides, preferably ethylene oxide, and higher unsaturated or saturated C₈-C₂₂fatty alcohols with C₁-C₁₀alkylisocyanates.

Interesting nonionic surfactants suitable as component (a) have the formula



wherein one of Y₁ and Y₂ is methyl or ethyl and the other is hydrogen,


n₁ is an integer from 2 to 40,

m₁ is an integer from 0 to 15, and

R and R₁ are as defined for formula (1).

- 5 -

Especially interesting nonionic surfactants are those of formula



wherein

R_2 is C_9 - C_{14} alkyl,


R_3 is hydrogen, C_1 - C_4 alkyl, a cycloaliphatic radical of at least 6 carbon atoms or a C_1 - C_{10} alkylisocyanato radical,

one of Y_3 and Y_4 is methyl and the other is hydrogen,

m_2 is an integer from 0 to 8, and

n_2 is an integer from 4 to 10.

Important nonionic surfactants are those of formula



wherein

R is an aliphatic radical of at least 8 carbon atoms,


R_4 is an unsubstituted or halogen substituted C_1 - C_{10} alkylisocyanato or an unsubstituted or by a hetero atom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical,

"alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and

p is an integer from 2 to 60.

Among these nonionic surfactants, those compounds are especially preferred in which the C_1 - C_{10} alkylisocyanato radical is n-butyliisocyanato or isopropylisocyanato.

Further important nonionic surfactants are those of formula



- 6 -

wherein

R_2 is C_9 - C_{14} alkyl,

R_5 is hydrogen or butyl,

one of Y_5 and Y_6 is methyl and the other is hydrogen,


m_3 is an integer from 0 to 3, and

n_3 is an integer from 4 to 8.

The nonionic surfactants of formula (4) are novel compounds. These compounds constitute a further object of the present invention.

The preparation of the end capped surfactants of formulae (1) to (5) is carried out in a manner which is known per se, conveniently by reacting the corresponding alkylene oxide polyadducts with thionyl chloride and subsequently reacting the resultant chlorinated compound with an alcohol of the formula R_1 -OH, wherein R_1 is alkyl or cycloalkyl.

If a compound of formula (4) is used as component (b), the known per se alkyl polyalkylene glycol ethers are reacted with C_1 - C_{10} alkylisocyanate using a catalyst or a mixture of catalysts according to the following reaction scheme:



wherein R , R_4 and p have the above defined meaning.

A mixture of nonionic surfactants may also be used as the nonionic surfactant (b).

The following compounds may suitably be used as optional component (c) of the composition of the invention:

- alkali metal salts and amine salts of C_1 - C_{10} alkylphosphoric acid esters;
- diols, such as hexylene glycol;
- sulfonates of terpenoids or mono- or binuclear aromatic compounds, for example the sulfonates of camphor, toluene, xylene, cumene and naphthol;
- alkali metal salts and amine salts of saturated or unsaturated C_3 - C_{12} di- or polycarboxylic acids, for example of malonic, succinic, glutaric, adipic, pimelic, suberic,

- 7 -

azelaic and sebacic acid, of undecanedicarboxylic and dodecanedicarboxylic acid, of fumaric, maleic, tartaric and malic acid as well as citric and aconitic acid.

2-Ethylhexyl sulfate is especially preferred.

It is preferred to use a textile auxiliary composition in which component (a) is polyacrylic acid, component (b) is a nonionic surfactant of formula (1) or a mixture of nonionic surfactants of formulae (1) to (5), and optional component (c) is 2-ethylhexyl sulfate.

A particularly interesting textile auxiliary composition is one wherein component (a) is polyacrylic acid and component (b) is a nonionic surfactant of formula (3), wherein R_3 is a C_1 - C_{10} alkylisocyanato radical and $m_2=0$.

The textile auxiliary composition of this invention can be prepared by simple stirring of components (a), (b) and optionally (c).

The composition is preferably prepared by mixing components (a), (b) and optionally (c), with stirring, and adding deionised water until a homogeneous solution is obtained.

The textile auxiliary composition of this invention has a pH in the range from 3 to 5, preferably from 3.5 to 4.5.

Preferred textile auxiliary composition of the invention conveniently comprises, based on the entire composition:

2 to 22 % by weight, preferably 5 to 18 % by weight, of component (a),
10 to 95 % by weight, preferably 25 to 60 % by weight, of component (b),
0 to 15 % by weight, preferably 1 to 10 % by weight, of component (c), and
and water to make up 100 % by weight.

The novel formulations is a low-foaming and nonsilicone textile auxiliary having soil dissolving properties. Owing to its liquid form, it is easy to handle and therefore especially suitable for modern metering devices. It has a multipurpose utility and is consequently suitable for different end use requirements.


It may be used as wetting agent, textile detergent, dispersant or stabiliser in peroxide

- 8 -

bleaching liquors.

Furthermore it is suitable as household washing agent.

Accordingly, the invention relates to a process for wetting, washing and/or bleaching fibre materials, which comprises treating said materials, in aqueous medium, in the presence of a textile auxiliary composition in which component (a) is a homopolymer of an ethylenically unsaturated sulfonic or carboxylic acid or an anhydride thereof, component (b) is a nonionic surfactant of formula



wherein

R is an aliphatic radical of at least 8 carbon atoms,

R₁ is hydrogen, C₁-C₈alkyl, a cycloaliphatic radical of at least 5 carbon atoms, styryl, an unsubstituted or halogen substituted C₁-C₁₀alkylisocyanato or an unsubstituted or by a hetero atom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical,

"alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and

p is an integer from 2 to 60, and optionally

(c) is a hydrotropic agent.

For this process it is preferred to use a textile auxiliary composition in which component (a) is a polyacrylic acid, component (b) is a nonionic surfactant of formula (3), wherein R₃ is n-butyl or a C₁-C₁₀alkylisocyanato radical, and m₂=0, and component (c) is a hydrotropic agent.

The amounts in which the textile auxiliary composition of the invention is added to the treatment liquors are from 0.1 to 60 g/litre, preferably from 0.2 to 10 g/litre, of treatment liquor. These liquors may contain further ingredients, such as desizing agents, dyes, fluorescent whitening agents, synthetic resins and alkalies such as sodium hydroxide, hydrogen peroxide and magnesium salts.

Suitable fibre materials are: cellulose, especially non-pretreated natural cellulose such as hemp, linen, jute, viscose staple, viscose, acetate rayon, natural cellulose fibres and, preferably, raw cotton, wool, polyamide, polyacrylonitrile or polyester fabrics and blends,

- 9 -

for example polyacrylonitrile/cotton or polyester/cotton blends.

The fibre material can be in any form of presentation, for example the cellulosic material may be in the form of loose stock, yarn, woven or knitted goods. The material is thus usually always in the form of textile materials which are made from pure cellulosic textile fibres or from blends of cellulosic textile fibres with synthetic textile fibres. The fibre material can be treated continuously or batchwise in aqueous liquor.

The aqueous treatment liquors can be applied to the fibre materials in known manner, conveniently by impregnation on the pad to a pick-up of ca. 70-120 % by weight. The pad method is used especially in the pad-steam and pad-batch process.

Impregnation can be effected in the temperature range from 10 to 60°C, but preferably at room temperature. After impregnation and expression, the cellulosic material is subjected to an optional heat treatment in the temperature range from 80 to 140°C. The heat treatment is preferably carried out by steaming at 95-140°C, preferably 100-106°C. Depending on the nature of the heat development and the temperature range, the heat treatment can take from 30 seconds to 60 minutes. In the pad-batch process, the impregnated goods are rolled up without being dried, packed in a plastic sheet, and stored at room temperature for 1 hour to 24 hours.

The treatment of the fibre materials can also be carried out in long liquors at a liquor to goods ratio of typically 1:3 to 1:100, preferably 1:4 to 1:25, and at 10 to 100°C, preferably 60 to 98°C, for ca. 1/4 to 3 hours under normal conditions, i.e. under atmospheric pressure, in conventional apparatus such as a jigger, jet or a winchbeck. If desired, the heat treatment can also be carried out in the temperature range up to 150°C, preferably from 105 to 140°C, under pressure in HT (high-temperature) apparatus.

If the process makes it necessary, the fibre materials are subsequently thoroughly rinsed with hot water of 90-98°C and then with warm and, finally, cold water, if appropriate neutralised, and then dried at elevated temperature.

In the following illustrative Examples percentages are always by weight.

Preparation of the nonionic surfactants which are end-capped with an isocyanato radical and suitable for use as component (b)

Example 1: 51 g (c. 0.1 mol) of the polyadduct of 1 mol of decyl alcohol and 8 mol of ethylene oxide are dissolved in 25 ml of dry tetrahydrofuran and to the solution are added 8.9 g (0.105 mol) of isopropyl isocyanate. After addition of a catalyst mixture consisting of 100 µl each of dibutyltin laurate and triethylamine, the reaction mixture is heated, with stirring, to 60°C under a stream of inert gas. The reaction is terminated after 90 minutes by pouring the reaction mixture into petroleum ether and isolating the almost colourless precipitate. The precipitate is dried at 50°C under vacuum to give 56.8 g of slightly oily product.

Example 2: 153 g (c. 0.3 mol) of the polyadduct of 1 mol of decyl alcohol and 8 mol of ethylene oxide are charged, without solvent, to a reactor in an inert gas atmosphere and 30.9 g (0.105 mol) of n-butyl isocyanate are added dropwise, with stirring. After addition of a catalyst mixture consisting of 100 µl each of dibutyltin laurate and triethylamine, slight warming of the reaction mixture to c. 40°C ensues initially. The reaction is fully complete after 60 minutes at a temperature of 60°C. Finally, the reaction mixture is poured into 100 ml of petroleum ether (40-80). The precipitated liquid product is isolated and dried at 50°C under vacuum. Yield: 167 g.

Example 3: 18.4 g (0.036 mol) of the polyadduct of 1 mol of decyl alcohol and 8 mol of ethylene oxide are dissolved in 25 ml of dry tetrahydrofuran. Then 4.8 g (0.038 mol) of tetrahydropyran-2-yl isocyanate are added dropwise in an inert gas atmosphere. To the well stirred batch is finally added a catalyst mixture consisting of 50 µl each of dibutyltin laurate and triethylamine. The reaction is fully complete after c. 100 minutes at a reaction temperature of 60°C. The batch is poured into 100 ml of petroleum ether, whereupon the highly viscous, milky-white product precipitates and is subsequently dried under vacuum. Yield: 23.6 g.

Example 4: 18.4 g (0.036 mol) of the polyadduct of 1 mol of decyl alcohol and 8 mol of ethylene oxide are dissolved in 25 ml of dry tetrahydrofuran. After addition of a catalyst mixture consisting of 100 µl each of dibutyltin laurate and triethylamine in an inert gas atmosphere, slight warming of the reaction mixture to c. 40°C ensues initially. Then 4.8 g (0.038 mol) of cyclohexylisocyanate are added dropwise. The reaction is fully complete after c. 200 minutes at a reaction temperature of 60°C. The batch is poured into 120 ml of petroleum ether, whereupon the lower, liquid phase of the colourless product is separated and subsequently dried under vacuum. Yield: 21.5 g.

Example 5: 12.5 g (0.021 mol) of the polyadduct of 1 mol of decyl alcohol and 11 mol of ethylene oxide are dissolved in 25 ml of dry tetrahydrofuran. Then 2.4 g (0.023 mol) of 2-chlorethyl isocynate and a catalyst mixture consisting of 50 μ l each of dibutyltin laurate and triethylamine are added. After areaction time of 20 hpurs at 60°C the product is isolated removing the volatile parts of the solution in high vaccum at 50°C. Yield: 14.4 g.

Preparation of the formulations

Example 6:

340 g of a 25 % polyacrylic acid having a molecular weight of 190 000 are added to
 247 g of deionised water.
 The pH is adjusted to 3.0 with
 8 g of 30 % sodium hydroxide solution. Then, with stirring,
 70 g of a 40 % solution of the sodium salt of 2-ethylhexyl sulfate,
 250 g of the nonionic surfactant of formula $R-O-(CH_2CH_2O)_{-8}-R_1$, wherein R is a $C_{9/11}$ alkyl radical and R_1 is butyl,
 34 g of the polyadduct of 1 mol of a C_{13} oxoalcohol and 9 mol of ethylene oxide, and
 51 g of the polyadduct of 1 mol of a C_{13} oxoalcohol and 10 mol of ethylene oxide
 are added in succession.

The slightly viscous formulation so obtained has a pH of 3 and a cloud point of c. 67°C.

Example 7:

340 g of a 25 % polyacrylic acid having a molecular weight of 243 000 are added to
 247 g of deionised water.
 The pH is adjusted to 3.0 with
 8 g of 30 % sodium hydroxide solution. Then, with stirring,
 70 g of a 40 % solution of the sodium salt of 2-ethylhexyl sulfate,
 250 g of the polyadduct of 1 mol of decyl alcohol and 5 mol of ethylene oxide/8 mol of propylene oxide, and
 95 g of the polyadduct of 1 mol of tridecyl alcohol and 9.75 mol of ethylene oxide

- 12 -

are added in succession.

The slightly viscous formulation so obtained has a pH of 3.5 and a cloud point of c. 46°C.

Example 8:

340 g of a 25 % polyacrylic acid having a molecular weight of 190 000 are added to
247 g of deionised water.

The pH is adjusted to 3.0 with

8 g of 30 % sodium hydroxide solution. Then, with stirring,

70 g of a 40 % solution of the sodium salt of 2-ethylhexyl sulfate,

250 g of the polyadduct of 1 mol of decyl alcohol and 8 mol of ethylene oxide and
1 mol of n-butyl isocyanate,

34 g of the polyadduct of 1 mol of a C₁₃oxoalcohol and 9 mol of ethylene oxide, and

51 g of the polyadduct of 1 mol of a C₁₃oxoalcohol and 10 mol of ethylene oxide

are added in succession.

The slightly viscous formulation so obtained has a pH of 4.1 and a cloud point of c. 58°C.

Application Examples

Example 9: The formulations prepared in Examples 4-6 are tested for their detergent properties. This is done by washing a polyester/cotton blend, which has been artificially soiled with soot and engine oil, in an Ahiba dyeing machine with twist for 30 minutes at 40°C and at a liquor to goods ratio of 1:25. The amount of active substance is 1 g/l and the pH of the wash liquor is adjusted to 10 with NaOH. At the end of the washing procedure, the fabric is rinsed, hydroextracted and dried.

The detergent properties are determined by measuring the difference in colour between the washed and an unwashed sample. The higher the reflectance, the better the detergent effect. The differences measured are reported in Table 1 (2).

The formulations are foamed in accordance with DIN 53 902, the measurements being made at room temperature using 200 ml of a wash liquor containing 1 g of active substance/l of the formulations of Examples 4, 5 and 6 [Table 1 (3)].

- 13 -

Example 10: Raw cotton tricot fabric is treated for 30 minutes at 90°C in a bleach bath which contains the following ingredients:

2 g/l of the formulations prepared according to Examples 4-6
 1 g/l of NaOH (100%), and
 5 ml/l of H₂O₂ (35%).

After bleaching, the fabric is washed off hot and cold, neutralised and dried.

The addition of the novel formulations results in a substrate of good absorbency being obtained after the bleach.

The whiteness level is increased from -77 to 56 CIBA-GEIGY whiteness units [Table 1(4)].

The wetting properties of the individual formulations is determined in accordance with DIN 53 901 [g/l for 25'' wetting time (=WT)]. The results are reported in Table 1 (1).

Table 1:

Test criteria	Formulation of Example 4	Formulation of Example 5	Formulation of Example 6
(1) wetting power (g/l for 25'' WT)	1.3	1.1	1.4
(2) detergent effect colour diff.abs.:	21.7	21.2	18.2
(3) foam height [ml] (immed./after 1')	50/50	90/80	80/70
(4) whiteness	56	56	56


Example 11: The formulations prepared in Examples 6 to 8 are stable for use in highly concentrated alkaline stock liquors containing up to 360 g/l of NaOH.

Example 12: A cotton/polyester blend (33:67) is printed on shade with a printing paste


- 14 -

comprising


20 g/kg of the dye of the formula



12 g/kg of the dye of the formula



5 g/kg of the dye of the formula



as well as 963 g/kg of a stock thickener comprising

40 parts of Permutit H₂O

4 parts of an ethoxylated fatty acid derivative

200 parts of an hydrocarbon compound, for example [®]Sangajol

- 15 -

400 parts	of sodium alginate 6 %
50 parts	of urea
15 parts	of NaHCO_3
291 parts	of Permutit water,

dried for 5 minutes at 90°C, and afterwards fixed in a fixation unit for 8 minutes at 180°C with superheated steam.

The printed material is given a wash-off in an AHIBA machine. For this purpose, two wash baths A and B are prepared with Permutit water. Wash bath A contains 3 g/l, based on 100 % of the goods, of the detergent formulation of Example 6. Wash bath B contains no further ingredients. The liquor ratio is 1:30. Three uniformly printed samples on a white ground are each washed in succession in the same bath for 5 minutes at 90°C. The samples are then rinsed 3 times within 2 minutes cold in Permutit water. After drying the material at 90 to 100°C, a print is obtained wherein the white fond is less soiled compared to a print which was not washed with the formulation according to the invention.

Example 13: The procedure of Example 12 is repeated, but using the formulation prepared in Example 6 for the wash-off.


- 16 -

What is claimed is:

1. A low-foaming, nonsilicone, aqueous textile auxiliary composition comprising

(a) a homopolymer of an ethylenically unsaturated sulfonic or carboxylic acid or an anhydride thereof,

(b) a nonionic surfactant of formula



wherein

R is an aliphatic radical of at least 8 carbon atoms,

R₁ is hydrogen, C₁-C₈alkyl, a cycloaliphatic radical of at least 5 carbon atoms, styryl, an unsubstituted or halogen substituted C₁-C₁₀alkylisocyanato or an unsubstituted or by a hetero atom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical,

"alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and

p is an integer from 2 to 60, and optionally

(c) a hydrotropic agent.


2. A textile auxiliary composition according to claim 1, wherein component (a) is a polymerised monocarboxylic acid of 3 to 5 carbon atoms, preferably polyacrylic acid or polymethacrylic acid.

3. A textile auxiliary composition according to either claim 1 or claim 2, wherein component (a) is polyacrylic acid.

4. A textile auxiliary composition according to claim 3, wherein the polyacrylic acid has a molecular weight in the range from 4000 to 2 000 000.

5. A textile auxiliary composition according to claim 1, wherein the nonionic surfactant of component (b) has the formula

- 17 -




wherein one of Y_1 and Y_2 is methyl or ethyl and the other is hydrogen,

n_1 is an integer from 2 to 40,

m_1 is an integer from 0 to 15, and

R and R_1 are as defined for formula (1).

6. A textile auxiliary composition according to claim 5, wherein the nonionic surfactant of component (b) has the formula



wherein

R_2 is C_9 - C_{14} alkyl,


R_3 is hydrogen, C_1 - C_4 alkyl, a cycloaliphatic radical of at least 6 carbon atoms or C_1 - C_{10} alkylisocyanato radical,

one of Y_3 and Y_4 is hydrogen or methyl and the other is hydrogen,

m_2 is an integer from 0 to 8, and

n_2 is an integer from 4 to 10.

7. A textile auxiliary composition according to claim 1, wherein component (b) is a nonionic surfactant of formula



wherein

R is an aliphatic radical of at least 8 carbon atoms,


R_4 is an unsubstituted or halogen substituted C_1 - C_{10} alkylisocyanato or an unsubstituted or by a hetero atom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical,

"alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and

p is an integer from 2 to 60.

8. A textile auxiliary composition according to claim 7, wherein R_4 is a n-butyliisocyanato or isopropylisocyanato radical.

9. A textile auxiliary composition according to claim 1, wherein component (b) has the formula



wherein

R_2 is C_9 - C_{14} alkyl,

R_5 is hydrogen or butyl,

one of Y_5 and Y_6 is methyl and the other is hydrogen,

m_3 is an integer from 0 to 3, and

n_3 is an integer from 4 to 8.

10. A textile auxiliary composition according to claim 1, wherein component (c) is 2-ethylhexyl sulfate.

11. A textile auxiliary composition according to any one of claims 1 to 10, wherein component (a) is polyacrylic acid, component (b) is a nonionic surfactant of formula (1) or a mixture of nonionic surfactants of formulae (1) to (5), and optional component (c) is 2-ethylhexyl sulfate.

12. A textile auxiliary composition according to claim 1, wherein component (a) is polyacrylic acid and component (b) is a nonionic surfactant of formula (3), wherein R_3 is a C_1 - C_{10} alkylisocyanato radical and $m_2=0$.

13. A textile auxiliary composition according to any one claims 1 to 12, which has a pH in the range from 3 to 5.

14. A textile auxiliary composition according to claim 1, which comprises, based on the composition:

- 19 -


2 to 22 % by weight of component (a),
 10 to 95 % by weight of component (b),
 0 to 15 % by weight of component (c), and
 and water to make up 100 % by weight.

15. Use of a textile auxiliary composition as claimed in any one of claims 1 to 14 as wetting agent, textile detergent, dispersant or as stabiliser in peroxide bleaching liquors.

16. A process for wetting, washing and/or bleaching fibre materials, which comprises treating said materials, in aqueous medium, in the presence of a textile auxiliary composition comprising

(a) a homopolymer of an ethylenically unsaturated sulfonic or carboxylic acid or an anhydride thereof,

b) a nonionic surfactant of formula



wherein

R is an aliphatic radical of at least 8 carbon atoms,

R₁ is hydrogen, C₁-C₈alkyl, a cycloaliphatic radical of at least 5 carbon atoms, styryl, an unsubstituted or halogen substituted C₁-C₁₀alkylisocyanato or an unsubstituted or by a hetero atom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical,

"alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and

p is an integer from 2 to 60, and optionally

(c) a hydrotropic agent.

17. A process according to claim 16, which comprises using a textile auxiliary composition wherein component (a) is a polyacrylic acid, component (b) is a nonionic surfactant of formula (3), wherein R₃ is n-butyl or a C₁-C₁₀alkylisocyanato radical and m₂=0, and component (c) is a hydrotropic agent.

18. A process according to either claim 16 or claim 17, wherein the textile auxiliary


- 20 -

composition is used in an amount of 0.1 to 60 g, preferably 0.2 to 10 g, per litre of liquor.

19. A process according to any one of claims 16 to 18, which comprises treating the fibre material continuously or batchwise.

20. The fibre material treated according to any one of claims 16 to 19.

21. A nonionic surfactant of formula



wherein

R is an aliphatic radical of at least 8 carbon atoms,

R₄ is an unsubstituted or halogen substituted C₁-C₁₀alkylisocyanato or an unsubstituted or by a hetero atom substituted cycloalkylisocyanato or cycloalkenylisocyanato radical,


"alkylene" denotes an alkylene radical of 2 to 4 carbon atoms, and

p is an integer from 2 to 60.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 92/00299

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶			
According to International Patent Classification (IPC) or to both National Classification and IPC			
Int.Cl. 5	C11D3/37; D06L1/14;	C11D1/72; D06M15/263;	C11D1/722; D06M15/356; D06L3/02 C08G65/32
II. FIELDS SEARCHED			
Minimum Documentation Searched ⁷			
Classification System	Classification Symbols		
Int.Cl. 5	D06L ; B01F	C11D ; D06M ;	C08G
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸			
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹			
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²		Relevant to Claim No. ¹³
X	EP,A,0 308 221 (ROHM AND HAAS CO.) 22 March 1989 see abstract; claims 1-8,11 ---		1-6,9, 11,14-16
X	EP,A,0 335 404 (LION CORP.) 4 October 1989 see page 4, line 29 - page 5, line 19; claims 1,4,5,7 ---		1-6,9, 11,15,16
X	EP,A,0 299 691 (DIVERSEY CORP.) 18 January 1989 see page 6, line 21 - line 37; claims 1-7 ---		1-6, 9-11, 14-16
X	GB,A,2 151 252 (SANDOZ LTD.) 17 July 1985 see page 2, line 7 - line 25; claims 1-4 ---		1-5,15, 16
-/- 0			
¹⁰ Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family			
IV. CERTIFICATION			
Date of the Actual Completion of the International Search 18 MAY 1992		Date of Mailing of this International Search Report 03.06.92	
International Searching Authority EUROPEAN PATENT OFFICE		Signature of Authorized Officer SERBETSOGLU A. 	

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		Relevant to Claim No.
Category °	Citation of Document, with indication, where appropriate, of the relevant passages .	
A	EP,A,0 360 736 (CIBA-GEIGY AG) 28 March 1990 see page 3, line 58 - line 61; claims 1,5,11-12 ---	1,5,15, 16
A	EP,A,0 114 788 (CIBA-GEIGY AG) 1 August 1984 see page 6, paragraph 2 - page 7, line 3; claims 1,4,9 ---	1,5,15, 16
A	EP,A,0 354 344 (HENKEL) 14 February 1990 see page 2, line 23 - page 3, line 24; claims 1-3 ---	1,5,10, 15,16
A	FR,A,2 342 365 (SOLVAY & CIE.) 23 September 1977 see claims 1-2; example 3 ---	1,2,15, 16
A	FR,A,2 107 169 (DEUTSCHE GOLD- UND SILBER-SCHNEIDANSTALT VORMALS ROESSLER) 5 May 1972 see page 14, line 31 - page 16, line 7; claims 1-2 ---	1,5,15, 16
X A	DE,A,1 954 080 (FARBWERKE HOECHST AG) 6 May 1971 see claims 1,4,5 ---	21 1,7,12, 16,17
A	EP,A,0 055 818 (TH. GOLDSCHMIDT AG) 14 July 1982 see page 4, line 27 - line 37; claims 1,6,8 ---	21
A	GB,A,2 075 038 (ICI LTD.) 11 November 1981 see claim 1; example ---	21
A	US,A,3 960 781 (R.E. FREIS ET AL.) 1 June 1976 see column 4, line 21 - column 6, line 60; claim 1 ---	21

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.**

EP 9200299
SA 56043

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 18/05/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0308221	22-03-89	AU-A- 2231488	23-03-89
		JP-A- 1158098	21-06-89
EP-A-0335404	04-10-89	JP-A- 1250473	05-10-89
		JP-C- 1580169	11-10-90
		JP-B- 2004709	30-01-90
EP-A-0299691	18-01-89	US-A- 4826618	02-05-89
		AU-B- 616417	31-10-91
GB-A-2151252	17-07-85	BE-A- 901196	04-06-85
		CH-A- 661743	14-08-87
		DE-A- 3443963	20-06-85
		FR-A- 2556364	14-06-85
		JP-A- 60141798	26-07-85
EP-A-0360736	28-03-90	JP-A- 2105897	18-04-90
		US-A- 5002686	26-03-91
EP-A-0114788	01-08-84	CA-A- 1227099	22-09-87
		JP-A- 59145237	20-08-84
		US-A- 4539353	03-09-85
EP-A-0354344	14-02-90	DE-A- 3823454	25-01-90
		JP-A- 2080662	20-03-90
		US-A- 5013327	07-05-91
FR-A-2342365	23-09-77	LU-A- 74434	12-09-77
		AT-B- 375970	25-09-84
		AU-B- 497796	11-01-79
		AU-A- 2190377	10-08-78
		BE-A- 851685	22-08-77
		CH-A, B 637798	31-08-83
		DE-A, C 2703876	01-09-77
		GB-A- 1524013	06-09-78
		JP-C- 1280551	13-09-85
		JP-A- 52103386	30-08-77
		JP-B- 60001360	14-01-85
		NL-A- 7702052	29-08-77
		SE-B- 434067	02-07-84

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. EP 9200299
SA 56043**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 18/05/92

Page 2

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-A-2342365		SE-A- 7702049	26-08-77
		US-A- 4363699	14-12-82
FR-A-2107169	05-05-72	AT-A, B 310908	15-09-73
		BE-A- 772373	17-01-72
		CH-A- 571057	31-12-75
		DE-A, B 2044601	16-03-72
		GB-A- 1350275	18-04-74
		NL-A- 7109990	13-03-72
DE-A-1954080	06-05-71	None	
EP-A-0055818	14-07-82	DE-A- 3100080	22-07-82
GB-A-2075038	11-11-81	JP-A- 57002325	07-01-82
US-A-3960781	01-06-76	US-A- 3899387	12-08-75